

Serial No. : 10/586,002
Filed : July 12, 2006

IN THE CLAIMS:

Please amend claims as follows:

1. (previously canceled)
2. (previously canceled)
3. (currently amended) A ball endmill comprising (a) a cylindrical tool body which is to be rotated about an axis thereof, and (b) ball-nosed end cutting edges which are located in an axially distal end portion of said tool body and which describe a semi-spherical-shaped locus during rotation of said tool body,

wherein each of said ball-nosed end cutting edges includes (b-1) a first portion extending from said axis and provided by a radially inner portion of each of said ball-nosed end cutting edges, and (b-2) a second portion contiguous to said first portion and provided by a radially outer portion of each of said ball-nosed end cutting edges,

wherein said first portion is defined by a circular arc which is convex in a direction of the rotation of said tool body and which has a first radius of curvature as ~~measured~~ seen in a distal end view ~~perpendicular to said axis~~, a ratio of said first radius of curvature to an outside diameter of said cylindrical body ~~being not smaller than 0.025 and not larger than 0.10~~ is in a range between 0.025 and 0.10,

and wherein said second portion is defined by a circular arc which is convex in said direction of the rotation of said tool body and which has a second radius of curvature as

Serial No. : 10/586,002
Filed : July 12, 2006

~~measured~~ seen in the distal end view ~~perpendicular to said~~
~~axis~~, said second radius of curvature ~~being~~ is larger than
said first radius of curvature.

4. (currently amended) The ball endmill according to claim
3, wherein said circular arc defining said first portion of each of
said ball-nosed end cutting edges has a central angle that is not
smaller than 60° and is not larger than 120° as measured in said
distal end view, where the central angle is an angle between a
first line connecting a center of the first radius and the axis and
a second line connecting the center of the first radius and a
connection point of said first portion and said second portion.

5. (previously introduced) The ball endmill according to
claim 3,

wherein said first and second portions of each of said
ball-nosed end cutting edges are connected to each other at a
connection point,

and wherein a first circle that is partially constituted
by said circular arc defining said first portion is inscribed
at said connection point to a second circle that is partially
constituted by said circular arc defining said second portion.

6. (previously introduced) The ball endmill according to
claim 3, further comprising (c) peripheral cutting edges each of
which is contiguous to said second portion of a corresponding one
of said ball-nosed end cutting edges and extends away from said

Serial No. : 10/586,002
Filed : July 12, 2006

axially distal end portion toward a shank portion of said tool body.

7. (currently amended) The ball endmill according to claim 3, wherein a ratio of said second radius of curvature to said outside diameter of said cylindrical body is ~~not smaller than 0.55 and not larger than 0.65~~ in a range between 0.55 and 0.65.

8. (previously introduced) The ball endmill according to claim 3, wherein said ball-nosed end cutting edges consist of at least three ball-nosed end cutting edges.

9. (currently amended) A ball endmill comprising (a) a cylindrical tool body which is to be rotated about an axis thereof, and (b) ball-nosed end cutting edges which are located in an axially distal end portion of said tool body and which describe a semi-spherical-shaped locus during rotation of said tool body,

wherein each of said ball-nosed end cutting edges includes (b-1) a first portion extending from said axis and provided by a radially inner portion of each of said ball-nosed end cutting edges, and (b-2) a second portion contiguous to said first portion and provided by a radially outer portion of each of said ball-nosed end cutting edges,

wherein said first portion is defined by a circular arc which is convex in a direction of the rotation of said tool body and which has a first radius of curvature as ~~measured~~ seen in a distal end view ~~perpendicular to said axis,~~

Serial No. : 10/586,002
Filed : July 12, 2006

and wherein said second portion is defined by a circular arc which is convex in said direction of the rotation of said tool body and which has a second radius of curvature as ~~measured~~ seen in the distal end view ~~perpendicular to said axis~~, said second radius of curvature ~~being~~ is different from said first radius of curvature.

10. (previously introduced) The ball endmill according to claim 9, wherein said second radius of curvature is larger than said first radius of curvature.